

Product Specifications	Kobetron™ GI-4000	Kobetron™ GI-4000 Pro
<b>Connectivity</b>		
RS-232	Yes	Yes*
USB	No	Yes
RFID	No	Yes (future)
Wi-Fi	No	Yes
Camera	No	Yes (future)
<b>Supported Memory Dev.</b>		
EPROMs	Yes	Yes
Micro Controllers	Yes	Yes
SIMMs	Yes	Yes
CashCode Memory	Yes	Yes
Firmware Hubs	Yes	Yes
DiskOnChips	No	Yes*
<b>Supported Storage Dev.</b>		
CompactFlash reader	Yes	Yes
CFAST reader	No	Yes
Thumb Drive	No	Yes
SATA/IDE Hard Disks	No	Yes*
<b>Supported Modules</b>		
MI-318 SIMM72 Standard	Yes	Yes
MI-319 SIMM80	Yes	Yes
MI-320 SIMM72 CG	Yes	Yes
MI-324 Unidesa S400	Yes	Yes
MI-326 CashCode Mem	Yes	Yes
MI-328 PLCC44 Atmel uC	Yes	Yes
MI-330 PLCC44-B LV	Yes	Yes
MI-331 CompactFlash	Yes	Built-in
MI-332 UniDIP	Yes	Yes
MI-333 UniPLCC32	Yes	Yes
<b>System Support</b>		
GAT	No	Yes
FAT32 Filesystem	No	Yes
NTFS Filesystem	No	Yes
ext2 Filesystem	No	Yes
ext4 Filesystem	No	Yes

Product Specifications	Kobetron™ GI-4000	Kobetron™ GI-4000 Pro
<b>Speed</b>		
27C322 (4MB)	5 Sec.	11.5 Sec.
25Q64BV (8MB)	15.7 Sec.	18.5 Sec.
32MB SIMM	14.5 Sec.	31.9 Sec.
CashCode Memory Stick	1 Min. 19 Sec.	7.8 Sec.
CashCode CCFS Stick	2 Min. 42 Sec.	9.1 Sec.
2GB CompactFlash	17 Min. 45 Sec.	6 Min. 43 Sec.
3.74GB CFAST	Not Supported	9 Min. 19 Sec.
<b>Product Detail</b>		
Display	4x20 Character LCD	7" Color LCD
Case Size	7.13" x 4.5" x 2.06"	11.17" x 5.86" x 2.11"
Case Material	ABS Plastic	ABS Plastic
Weight	1.5 Lbs.	2.8 Lbs.
Battery	4 Cell Lithium-Ion	4 Cell Lithium-Ion
Battery Size	8.4 Volt, 4400mAh	8.4 Volt, 6400mAh
Battery Run Time	10-12 Hrs	6-8 Hrs
Carrying Case	Soft Padded	Double-Sided Alum.
User Interface	Membrane Keypad	Touchscreen
Field Upgradeable	Yes*	Yes
GLI Access Database	Via external PC	Built-in
<b>Verification Capabilities</b>		
4-digit Kobetron sigs	Yes	Yes
8-digit Kobetron sigs	Yes	Yes
40-digit Kobetron sigs	Yes	Yes
CDCK-16 signatures	No	Yes
md5 signatures	No	Yes
SHA-1 signatures	Yes**	Yes
Simultaneous signatures	No	Yes